# YAOLAN PRECISION

Engineering reference | Product catalog

Illustrative catalog data. Not a certified engineering specification.

Confirm all dimensions, ratings and material grades with our sales team.

## YL-BV304 | 3-Piece Threaded Ball Valve



Material: SS304

Pressure: 1000 WOG

Connection: Threaded NPT/BSP

Actuation: Manual

Size range: 1/4–4 in

## YL-BV316 | 2-Piece Flanged Ball Valve



Material: SS316L

Pressure: Class 150

Connection: Flanged

Actuation: Manual

Size range: 1/2–8 in

## YL-GV150 | Flanged Rising Stem Gate Valve



Material: Carbon Steel WCB

Pressure: Class 150

Connection: Flanged

Actuation: Manual

Size range: 2–12 in

dcykj@foxmail.com | +86 13837786010

# YAOLAN PRECISION

Engineering reference | Product catalog

Illustrative catalog data. Not a certified engineering specification.

Confirm all dimensions, ratings and material grades with our sales team.

## YL-BF16 | Wafer Butterfly Valve



Material: SS316L

Pressure: PN16/PN40

Connection: Wafer

Actuation: Manual

Size range: 2–12 in

## YL-CV300 | Flanged Swing Check Valve



Material: SS316L

Pressure: Class 300

Connection: Flanged

Actuation: Self-actuated

Size range: 2–10 in

## YL-TF316 | Stainless Steel Compression Fittings



Material: SS316L

Pressure: 1000 WOG

Connection: Threaded NPT/BSP

Actuation: Manual

Size range: 1/4–1 in

dcykj@foxmail.com | +86 13837786010

# YAOLAN PRECISION

Engineering reference | Product catalog

Illustrative catalog data. Not a certified engineering specification.

Confirm all dimensions, ratings and material grades with our sales team.

## YL-PA100 | Rack & Pinion Pneumatic Actuator



Material: Aluminum

Pressure: Air supply

Connection: ISO 5211

Actuation: Pneumatic

Size range: ISO 5211

## YL-PBV316 | Pneumatic 3-Piece Ball Valve



Material: SS316L

Pressure: 1000 WOG

Connection: Threaded NPT/BSP

Actuation: Pneumatic

Size range: 1/2–4 in

## YL-BV300 | High-Pressure Flanged Ball Valve



Material: Carbon Steel WCB

Pressure: Class 300

Connection: Flanged

Actuation: Manual

Size range: 1/2–6 in

dcykj@foxmail.com | +86 13837786010

# YAOLAN PRECISION

Engineering reference | Product catalog

Illustrative catalog data. Not a certified engineering specification.
Confirm all dimensions, ratings and material grades with our sales team.

## YL-GV316 | Stainless Steel Flanged Gate Valve



Material: SS316L
Pressure: Class 300
Connection: Flanged
Actuation: Manual
Size range: 2–10 in

## YL-BF40 | High-Performance Wafer Butterfly Valve



Material: SS304
Pressure: PN16/PN40
Connection: Wafer
Actuation: Manual
Size range: 2–12 in

## YL-CV150 | Stainless Steel Swing Check Valve



Material: SS304
Pressure: Class 150
Connection: Flanged
Actuation: Self-actuated
Size range: 2–8 in

dcykj@foxmail.com | +86 13837786010

# YAOLAN PRECISION

Engineering reference | Product catalog

Illustrative catalog data. Not a certified engineering specification.

Confirm all dimensions, ratings and material grades with our sales team.

## YL-TF304 | Instrumentation Tube Union & Tee



Material: SS304

Pressure: 1000 WOG

Connection: Threaded NPT/BSP

Actuation: Manual

Size range: 1/4–1 in

## YL-PA200 | Double-Acting Rotary Actuator



Material: Aluminum

Pressure: Air supply

Connection: ISO 5211

Actuation: Pneumatic

Size range: ISO 5211

## YL-BV320 | Butt-Weld Ball Valve Series



Material: SS316L

Pressure: Class 300

Connection: Butt Weld

Actuation: Manual

Size range: 1/2–4 in

dcykj@foxmail.com | +86 13837786010

# YAOLAN PRECISION

Engineering reference | Product catalog

Illustrative catalog data. Not a certified engineering specification.

Confirm all dimensions, ratings and material grades with our sales team.

## YL-PBV304 | Pneumatic Isolation Ball Valve



Material: SS304

Pressure: 1000 WOG

Connection: Threaded NPT/BSP

Actuation: Pneumatic

Size range: 1/2–4 in

dcykj@foxmail.com | +86 13837786010